



Broadband PM Optical Isolator 1064±50nm

The 1064±50nm Broadband Polarization Maintaining (PM) Optical Fiber Isolator is an in-line micro-optic component allows light to be transmitted only in the forward direction while blocking the backward transmission. It's built with PM Panda fiber and designed to maintain the polarization of the input light with high extinction ratio. The PM isolators are commonly used to protect lasers or amplifiers against back-reflected light. High power available upon request.



Features

- High Isolation
- High Extinction Ratio
- High Power Available upon Request



Applications

- Fiber Amplifier
- Fiber Laser
- Fiber Sensor
- High Speed Optical Communications Instrumentations

Performance Specification

Parameter	Value	Unit
Center Wavelength	1064 or customized	nm
Bandwidth	±50	nm
Typ. Peak Isolation	33	dB
Min. Isolation at 23°C	26	dB
Typ. Insertion Loss at 23°C	1.0	dB
Max. Insertion Loss at -5 to 50°C	1.5	dB
Min. Extinction Ratio for Fast Axis Blocked Type	22	dB
Min. Extinction Ratio for Both Axis Working Type	20	dB
Min. Return Loss	50	dB
Max. Optical Power (Continuous Wave)	500 (higher power available upon request)	mW
Max. Tensile Load	5	N
Fiber Type	PM 980 Panda Fiber on Input & Output Port	
Operating Temperature	-5 to +50	°C
Storage Temperature	-40 to +85	°C
Package Dimension	Φ5.5×L35	mm

Note

* For devices with connectors, IL will be 0.3dB higher, RL will be 5dB lower and ER will be 2dB lower.
 * The PM fiber and the connector key are aligned to the slow axis.

Ordering Information

BPMI-AAAA-B-CC-DD-E

AAAA	B	CC	DD	E
Wavelength	Fiber Jacket	Fiber Length	Connector	Working Axis
1050 - 1050nm	B - 250um Bare	05 - 0.5m	NE - None	F - Fast Axis
1064 - 1064nm	Fiber	08 - 0.8m	FA - FC/APC	Blocked
SSSS - Specify	L - 900um Loose	10 - 1.0m	FP - FC/PC	B - Both Axis
	Tube	15 - 1.5m	SA - SC/APC	Operating
		SS - Specify	SP - SC/PC	
			LA - LC/APC	
			LP - LC/PC	
			SS - Specify	